



## “MESH” – HEAVY COMMERCIAL SOLUTION DYED NYLON TILE

Product definition	ISO 2424	Scroll loop pile
Gauge	ISO 2424	1/10"
No. of tufts	ISO 1763	177,750 m <sup>2</sup>
Pile fibre	ISO 2424	100% solution dyed Nylon (PA 6)
Pile weight	ISO 8543	575gr/m <sup>2</sup> ± 10%
Total weight	ISO 8543	3900gr/m <sup>2</sup> ± 7.5%
Pile height	ISO 1765	2.5mm ± 5%
Total thickness	ISO 1765	5.5mm ± 5%
Tile backing	ISO 2424	Bitumen with a fibreglass scrim
Tile size		500mm × 500mm (20 tiles/box = 5m <sup>2</sup> )
Planks size		250mm × 1000mm (Special Order ONLY)
Use classification	Method EN 1307	Class 33 Heavy Commercial
Castor chair test	EN 985	A, continuous use
Luxury / comfort	EN 1307	LC1
Sound absorption	ISO 10140	25dB (31dB with Acoustic Backing)
Electrostatic charging	ISO 6536	<2kV
Static loading		Anti-static
Dimensional stability	EN 986	Pass
Reaction to fire	ISO 11925-2 / ISO 9239-1	Bfl-s1
Abrasion	ISO 12951	Pass
Vettermann test	ISO 10361/EN 1471	Pass
Rubbing, wet AND dry	ISO 105-X12	5.0
Water	ISO 105 E01	≥ 4
Light	ISO 105 B02	≥ 5
Wear warranty		10 Year Commercial



**TILES: 500 × 500mm**  
**PLANKS: 250 × 1000mm (available by Special Order only)**



**31dB WHEN ORDERED WITH ACOUSTIC BACKING (25dB is standard rating)**

### GENERAL

<b>Planks and Acoustic Backing</b>	Both are available on Special Order only – please ask for more details
<b>Suitability</b>	Heavy Commercial Use areas: office, retail, hospitality, leisure and educational
<b>Recommended Maintenance</b>	Please refer to our website for installation and maintenance guidelines for details of suitability.
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards. Areas larger than 30m <sup>2</sup> – it is advised that a suitable tackifier be used.
<b>Dye Lots</b>	Colours may vary from batch to batch, it is therefore advised when ordering a large continuous area, tiles of the same batch are specified when ordering.
<b>Pile Direction</b>	Best results are obtained when using the illustrated laying patterns.
<b>Warranties</b>	All warranties are subject to CCTUK T&C (available on request).

For a brochure, photos and more information, please visit [www.meshcarpettiles.co.uk](http://www.meshcarpettiles.co.uk)

**commercialcarpettilesuk.co.uk**  
**Tel: 01793 317940 Email: sales@cctuk.ltd**  
 29A Athena Avenue, Swindon, SN2 8EJ

